






Electrical :
Frequency Range : 0~GHz

Finish [Unit of Plating Thickness Is in Micro Inch(μ)]
1. Nickel Plating Thk. : 60 μ"min. (Under Plating)
2. Gold Plating Thk. : 1~2 μ"max. (Over Finish 1)

Item	Description	Material	Finish
1	Body	Brass	Finish 1/2
2	Outer Contact	BeCu	Finish 1/2
3	Insulator	PTFE	None
4	Inner Contact	Brass	Finish 1/2
5	Ferrule	Brass	Finish 1/2
6	Spacer	POM	None
7	Cap	Brass	Finish 1/2



Recommended Cable
Stripping Dimensions



Recommended Crimping
Dimensions for Ferrule

DO NOT SCALE
Unit of Measure: millimetres (mm)

Third Angle Projection

Designed by
Martin Smith

X.X - +-0.20
X.XX - +-0.10
X.XXX- +-0.05

Design Right
Protected

©2025

Date
20 jan 2025

A3

RoHS
Compliant

Cambridge
Electronic
Industries Ltd

This document and all the data
contained herein is and shall remain
the property of Cambridge Electronic
Industries Ltd and may not be used
or copied for any purpose
whatsoever without the written
permission of Cambridge Electronic
Industries Ltd.

Description:
MCX Right Angle Crimp Plug for RG174

Part No:
ZJP-06-CRA-GGAD

Issue
1.0

Sheet
1 / 1

REVISION HISTORY				
REV	DESCRIPTION	CHG REF	DATE	DESIGNER
1.0	Origin	-	20/Jan/2025	M. Smith