




Specifications:
Current Rating: 4A (2~5P); 2A (6~8P); 1.5A (9~12P) AC/DC
Voltage Rating: 250V (2~4P); 60V (5P); 30V (6~12P) AC/DC
Contact Resistance: 5m ohm Max.
Insulation Resistance: 100M ohm Min.
Withstanding Voltage: 500V AC/Minute
Operating Temperature Range: -40°C ~ +100°C
Waterproof Rate: IP67

CC12-XXP-FA07-PBX
Panel Lock Thread
Panel Mount PCB Dip
Die Casting
Front Fastened A Coding
Plug
No. of Positions
M12



ITEM	Description	Material	Remark	Q'TY
1	Insulator	Nylon	UL94V-0 Black	1
2	Terminal	Copper Alloy	Gold Plated 1u"	2~12
3	Shell	Zinc Alloy	Nickel Plated 60u"	1
4	Seal ring	Silicone	Red	1
5	Nut	Copper Alloy	PG9 or M16 Nickel Plated 60u"	1

DO NOT SCALE

Unit of Measure: millimetres (mm)

Third Angle Projection

Designed by

Owen Page

X.X - +0.30

X.XX - +0.20

Design Right

Protected

©2023

Date

22 08 2023

A4

Issue

1.0

Sheet

1 / 1

Cambridge Electronic Industries Ltd

This document and all the data contained herein is and shall remain the property of Cambridge Electronic Industries Ltd and may not be used or copied for any purpose whatsoever without the written permission of Cambridge Electronic Industries Ltd.

Description:

M12 A Code Plug Straight Dip Type

Part No:

CC12-XXP-FA07-PBX