


General Description


The SCA08-XXPRX-XXXX is an M8 rear fastening panel mounted plug cable assembly with a stub end for completion with a termination of your choice. The M8 plug is available in an A or B coding with 2 to 8 pin options. The cable is available in a standard length of 50 or 300mm, but we can offer a bespoke cable assembly to any length and with any termination.



Specification	
Coding	A or B
Contact	2 to 8 Pins
Current Rating	3A AC/DC (2 to 5 Pins) 1.5A AC/DC (6 to 8 Pins)
Voltage Rating	60V AC/DC (2 to 3 Pins) 30V AC/DC (4 to 8 Pins)
Contact Resistance	≤5mΩ
Insulation Resistance	Cable ≥10MΩ Connector ≥100MΩ
Withstanding Voltage	500V AC/Minute (2 to 5 Pins) 250V AC/Minute (6 to 8 Pins)
Operating Temperature	-40 to +85°C
Waterproof Rate	IP67
Connector Part Number	CC08-XXP-RX-PM
Cable	UL1007 XXAWG

SCA08-XXPRX-XXXX

Cable Length
 0050: 50mm
 0300: 300mm
 Coding: A or B
 Rear Fastened
 Plug
 No. of Contacts



Pin Assignments Front View

A Coding	2 Pins	3 Pins	4 Pins	6 Pins	8 Pins	B Coding	5 Pins
Pin Outs	1. Black 3. Brown	1. Black 3. Brown 4. Red	1. Black 2. White 3. Brown 4. Red	1. Black 2. White 3. Brown 4. Red 5. Yellow 6. Blue	1. Black 2. White 3. Brown 4. Red 5. Yellow 6. Blue 7. Orange 8. Green		1. Black 2. White 3. Brown 4. Red 5. Yellow