

6 5 4 3 2 1

D

D

2P PIN OUT:

P1
1 Black
3 Brown

3P PIN OUT:

P1
1 Black
3 Brown
4 Red

4P PIN OUT:

P1
1 Black
2 White
3 Brown
4 Red

5P PIN OUT:

P1
1 Black
2 White
3 Brown
4 Red
5 Yellow



6P PIN OUT:

P1
1 Black
2 White
3 Brown
4 Red
5 Yellow
6 Blue



8P PIN OUT:

P1
1 Black
2 White
3 Brown
4 Red
5 Yellow
6 Blue
7 Orange
8 Green

Pin Assignments Front View

B Coding				
A Coding				

Item	Part No.	Description	Quantity
1	CC08-XXP-RX-PM	M8 Plug Rear Fastened Solder Type	1
2		Heat Shrink Tube, Colour: Black	A/R
3		UL1007 XXAWG, Colour: XX	A/R



SCA08-XXPRX-XXXX


Cable Length
0050: 50mm
0300: 300mm

Coding: A or B

Rear Fastened


Plug

No. of Contacts



Recommended
Panel CUT-Out
Thickness:Max 3.5MM

REVISION HISTORY					
REV	DESCRIPTION	CHG REF	DATE	DESIGNER	
1.0	Origin	-	22 08 2023	Owen Page	

DO NOT SCALE Third Angle Projection Designed by Owen Page X.X - +0.50
Unit of Measure: millimetres (mm)  X.XX - +0.30 Design Right Protected ©2023 Date 22 08 2023 A4

RoHS Compliant Cambridge Electronic Industries Ltd This document and all the data contained herein is and shall remain the property of Cambridge Electronic Industries Ltd and may not be used or copied for any purpose whatsoever without the written permission of Cambridge Electronic Industries Ltd. Description: M8 Plug Rear Fastened Wire Harness

Part No: SCA08-XXPRX-XXXX Issue 1.0 Sheet 1 / 1