

Specifications:


Current Rating: 30A+5A
Voltage Rating: 500V
Contact Resistance: 2 ohm Max.
Insulation Resistance: 30M ohm Min.
Withstanding Voltage: 500V AC/Minute
Operating Temperature Range: -20°C - +80°C
Waterproof Rate: IP67

MCM-06PR-5A-XXXX

- Cable Length
- 0300: 300mm
- 0500: 500mm
- Right Angle Type
- Plug
- No. of Positions

PIN OUT:

P1	
1	Brown
2	White
3	Blue
4	Black
5	Grey
6	Green



Item	Description	Material	Quantity
1	Body	PPO Black	1
2	Plug Pin	Brass Gold Plated Over Nickel	6
3	Over Mold	TPU Black	1
4	Inner Mold	ABS Natural	1
5	Cable	UL2465 10AWG*2C+24AWG*4C+AL OD:9.0 Black	1

RoHS Compliant

Cambridge Electronic Industries Ltd

This document and all the data contained herein is and shall remain the property of Cambridge Electronic Industries Ltd and may not be used or copied for any purpose whatsoever without the written permission of Cambridge Electronic Industries Ltd.

Description:
Hook Type R/A Plug Cable
Part No:
SCM-06PR-5A-XXXX

Description: Hook Type R/A Plug Cable	Issue 1.0	Sheet 1 / 1
Part No: SCM-06PR-5A-XXXX		

REVISION HISTORY				
REV	DESCRIPTION	CHG REF	DATE	DESIGNER
1.0	Origin	-	29/08/2023	Owen Page
Designed by Owen Page	X.X - +-0.50 X.XX - +-0.30	Design Right Protected	©2023 29/08/2023	Date A4
All rights reserved. No part of this document may be reproduced without the express written permission of the author.				

REVISION HISTORY
