

Specification:
Current Rating: 1A
Rating: 60V
Contact Resistance: 5 ohm Max.
Insulation Resistance: 10M ohm Min. DC 450V
Operating Temperature Range: -20°C ~ +80°C
IP Rating: IP67 in Locked Condition


SCM05-XXPASS-XXXX

- Cable Length
- With Shielding
- Straight
- A Coding
- Plug
- No. of Contacts

Pin	Pin Assignments Front View	Part No.	Cable Length	Cable Gauge	Pin Out
3 Pin		SCM05-03PASS-0300	300+/-20mm	26AWG	1.Black 2.Blue 3.Green Shell Braid
		SCM05-03PASS-2000	2000+/-60mm		
		SCM05-03PASS-3000	3000+/-70mm		
		SCM05-03PASS-20000	20000+/-300mm		
4 Pin		SCM05-04PASS-0300	300+/-20mm	26AWG	1.Black 2.Brown 3.Blue 4.Green Shell Braid
		SCM05-04PASS-2000	2000+/-60mm		
		SCM05-04PASS-3000	3000+/-70mm		
		SCM05-04PASS-20000	20000+/-300mm		

Item	Part No.	Description	Quantity
1	CC05-XXP-A-MMS	M5 A Code Plug Shielding Solder Type	1
2		UL2464 26AWG*XXC+AB PVC Jacket Colour: Black	1
3		PE Inner Molding Colour: White	A/R
4		45P PVC Molding Colour: Black	A/R

DO NOT SCALE
Unit of Measure: millimetres (mm)



Designed by
Owen Page

X.X - +0.50
X.XX - +0.30

**Design Right
Protected**

©2023

Date
22 08 2023

A4
Owen Page

**RoHS
Compliant**

**Cambridge
Electronic
Industries Ltd**

This document and all the data
contained herein is and shall remain
the property of Cambridge Electronic
Industries Ltd and may not be used
or copied for any purpose
whatsoever without the written
permission of Cambridge Electronic
Industries Ltd.

Description:
M5 Over-Moulding Cables

Part No:
SCM05-XXPASS-XXXX

Issue
1.0

Sheet
1 / 1