

Specifications:

Standard: IEC 61076-2-104

Current Rating: 3A(2-5P); 1A(6-8P); AC/DC

Voltage Rating: 60V(2-3P); 30V(4-8P) AC/DC

Contact Resistance: 5 ohm Max.


Insulation Resistance: 100M ohm Min. DC 450V

Operating Temperature Range: -40°C - +80°C

Waterproof Rate: IP67

REVISION HISTORY										
REV	DESCRIPTION				CHG REF	DATE		DESIGNER		
1.0	Origin				-	29/08/2023		Owen Page		
Designed by Owen Page		X.X - +0.50 X.XX - +0.30		Design Right Protected		©2023		Date 29/08/2023		A4

DO NOT SCALE



Designed by Owen Page

X.X	- +-0.50
X.XX	- +-0.30

**Design Right
Protected**

©2023

Date	29/08/2023
------	------------

	A4	
--	----	--

**RoHS
Compliant**

**Cambridge
Electronic
Industries Ltd**

This document and all the data contained herein is and shall remain the property of Cambridge Electronic Industries Ltd and may not be used or copied for any purpose whatsoever without the written permission of Cambridge Electronic Industries Ltd.

in nic	Description: M8 Plug Over-Moulding Cables	
-----------	--	--

Part No:
SCM08-XXPXSS-XXXX

Issue	1.0
-------	-----

Sheet
1 / 1