

12GHz Micro BNC Coaxial Connectors

Micro BNC Cable Terminated Free Socket for 12G Applications

Part Number XPT-D002-NGBA

General Description

Our range of 12GHz Precision Micro BNC coaxial connectors are optimised for 4K/Quad HD and Ultra HD Broadcast applications and have been developed under the CoaxVision™ Brand name, while meeting the JIJA CoaXPress specification. These high performance connectors allow you to achieve a 12GHz channel in one single connection. The Micro BNC connectors are mateable with any standard Micro BNC connector, but optimum performance is achieved when PCB mounted styles are interfaced with these Cambridge Connectors 12GHz Micro BNC plugs, designed for use with 12GHz cable (such as Belden 1855A).



The XPT-D002-NGBA connector is a cable mounted Micro BNC free socket, which can be used with Belden cables for 12G applications and has a bayonet coupling.

Electrical Specification





Impedance:	75Ω
Frequency Range:	0-12GHz
Working Voltage:	500Vrms
Dielectric Withstanding Voltage:	1000Vrms
Contact Resistance:	Centre contact $\leq 3\text{m}\Omega$ Outer contact $\leq 2.5\text{m}\Omega$
Insulation Resistance:	$\geq 5\text{ G }\Omega$
Connector Type:	Female
Materials	
Centre Pin:	BeCu / 3 $\mu\text{"Au}$
Metal Parts:	Brass/Ni
Insulators:	PTFE
Environmental	
Temp Range:	-65 to +165°C
Mating Cycles:	500

Features


- Precision 12GHz 75Ω Micro BNC Cable Terminated Connectors
- Optimised for 4K/Quad HD and Ultra HD Broadcast Applications
- One single connection for each 12GHz Channel

12GSDI

CoaxVision™



Recommended Cable Stripping Dimensions



Recommended Crimping Dimensions for Ferrule



CAMBRIDGE
ELECTRONIC INDUSTRIES

Tel: +44 (0)1223 860041

Tel: +44 (0)1223 863377

Email: sales@cambridgeelectronics.com