








2~5 Pin








6~8 Pin



Recommended panel cutout
MAX panel thickness: 3.5



Electrical:

Current rating	3A (2 ~ 5 Pins), 1A (6 ~ 8 Pins) AC/DC
Voltage rating	60V (2 ~ 3 Pins), 30V (4 ~ 8 Pins) AC/DC
Withstanding voltage	500V AC/minute between contacts (2 ~ 5 Pins)
	250V AC/minute between contacts (6 ~ 8 Pins)
Insulation resistance	100MΩ MIN
Contact resistance	5mΩ MAX

Environmental:

Operating temperature	-40°C ~ +100°C
Ingress protection	IP67

CC08-XXS-RX-PM
- M8
- No. of contacts
- Socket
- Rear fastened
- Coding
- Panel mount solder

PARTS LIST				
ITEM	DESCRIPTION	MATERIAL	REMARK	QTY
1	Insulator	Nylon	UL94V-0 Black	1
2	Terminal	Copper Alloy	Gold Plated 3µ"	2~8
3	Shell	Copper Alloy	Nickel Plated 60µ"	1
4	Seal Ring	Silicone	Red	2
5	Nut	Copper Alloy	Nickel Plated 60µ"	1

REVISION HISTORY				
REV	DESCRIPTION	CHG REF	DATE	DESIGNER
1.0	Origin		21/08/2023	Owen Page
1.1	Drawing Update	FB/SUP	30/09/2026	Martin Smith

Design Right Protected

Third Angle Projection

RoHS Compliant

Material:

Finish:

Gen Tol
X. ±0.3
.X ±0.2
.XX ±0.15

DO NOT SCALE

Unit of Measure: millimeters (mm)

Designed by Owen Page

Checked by Peter Millard

Approved by

©2026

Date 21 Aug 2023

A3

CAMBRIDGE ELECTRONIC INDUSTRIES

This document and all the data contained herein is and shall remain the property of Cambridge Electronic Industries Ltd and may not be used or copied for any purpose whatsoever without the written permission of Cambridge Electronic Industries Ltd.

Description:
M8 (X) Pin A/B Code Socket, Rear Fastening, Straight Solder Bucket

Part No: CC08-XXS-RX-PM

Issue 1.1

Sheet 1 / 1

Source:E:\Cambridge Connectors\Live Products\Engineering Data\(CC#) M-Connectors\M8