




	A CODE	D CODE
2 PIN	① ③	① ③
3 PIN	① ④ ③	① ④ ③
4 PIN	① ② ④ ③	① ② ④ ③
5 PIN	① ② ⑤ ④ ③	① ② ⑤ ④ ③
6 PIN	① ② ⑦ ③ ⑥ ④	
7 PIN	① ② ⑦ ③ ⑥ ⑤ ④	
8 PIN	① ② ⑦ ⑧ ③ ⑥ ⑤ ④	
9 PIN	① ② ⑨ ③ ⑧ ④ ⑦ ⑥ ⑤	
10 PIN	① ② ⑨ ⑩ ③ ⑧ ④ ⑦ ⑥ ⑤	
11 PIN	① ② ⑨ ⑩ ③ ⑧ ⑪ ④ ⑦ ⑥ ⑤	
12 PIN	① ② ⑨ ⑩ ③ ⑧ ⑫ ⑪ ④ ⑦ ⑥ ⑤	












PG9 Recommended panel cutout
MAX panel thickness: 4.0



M16 Recommended panel cutout
MAX panel thickness: 4.0

Electrical:

Current rating	4A (2 ~ 5 Pins), 2A (6 ~ 8 Pins), 1.5A (9 ~ 12 Pins) AC/DC
Voltage rating	250V (2 ~ 4 Pins), 60V (5 Pins), 30V (6 ~ 12 Pins) AC/DC
Withstanding voltage	500V AC/minute between contacts
Insulation resistance	100MΩ MIN
Contact resistance	5mΩ MAX

Environmental:

Operating temperature	-40°C ~ +100°C
Ingress protection	IP67
Mating cycles	500

CC12-XXS-FX-PBSX

- Panel lock thread: 1=PG9 2=M16
- With shielding
- Panel mount PCB dip
- Coding A/D
- Front fastened
- Socket
- No. of contacts
- M12

PARTS LIST				
ITEM	DESCRIPTION	MATERIAL	REMARK	QTY
1	Insulator	Nylon 9T	UL94V-0 Black	1
2	Terminal	Copper Alloy	Gold Plated	2~12
3	Shell	Zinc Alloy	Nickel Plated	1
4	Seal Ring	Silicone	Red	2
5	Nut	Copper Alloy	PG9 or M16 Nickel Plated	1

REVISION HISTORY				
REV	DESCRIPTION	CHG REF	DATE	DESIGNER
1.0	Origin	-	29/08/2023	Owen Page
1.1	Updated Drawing	FB / SUPP	23 Sep 2026	Martin Smith

Design Right Protected

Third Angle Projection

RoHS Compliant

Material: Generic

Finish:

Gen Tol .X ±0.30 .XX ±0.20

DO NOT SCALE

Unit of Measure: millimeters (mm)

Designed by Owen Page

Checked by Peter Millard

Approved by

©2026

Date 29 Aug 2023

A3

CAMBRIDGE ELECTRONIC INDUSTRIES

This document and all the data contained herein is and shall remain the property of Cambridge Electronic Industries Ltd and may not be used or copied for any purpose whatsoever without the written permission of Cambridge Electronic Industries Ltd.

Description: M12 (X) Pin A/D Code Socket, Front Fastening, (PG9/M16 Thread), Straight PCB Solder, Shielded

Part No: CC12-XXS-FX-PBSX


Issue 1.1

Sheet 1 / 2


Source:E:\Cambridge Connectors\Live Products\Engineering Data\(CC#) M-Connectors\M12

Recommended PCB footprint
TOL: ±.05


2~5 Pins



6~8 Pins



9~12 Pins



Design Right Protected	Material:	Finish:	Gen Tol .X ±0.30 .XX ±0.20	DO NOT SCALE	Unit of Measure: millimeters (mm)
Third Angle Projection	Designed by: Owen Page	Checked by: Peter Millard	Approved by:	©2026	Date: 29 Aug 2023 — A3
RoHS Compliant	CAMBRIDGE ELECTRONIC INDUSTRIES	This document and all the data contained herein is and shall remain the property of Cambridge Electronic Industries Ltd and may not be used or copied for any purpose whatsoever without the written permission of Cambridge Electronic Industries Ltd.	Description: M12 (X) Pin A/D Code Socket, Front Fastening, (PG9/M16 Thread), Straight PCB Solder, Shielded		
			Part No: CC12-XXS-FX-PBSX	Issue: 1.1	Sheet: 2 / 2